

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: A METER TO INTERNET PATHWAY

APPLICANT: JOHN GERALD VAN HETEREN

07057-043001

CERTIFICATE OF MAILING BY EXPRESS MAIL

Express Mail Label No. EL 444261819US

June 1, 2000
Date of Deposit

A METER TO INTERNET PATHWAY

Sub
DI

Cross-Reference to Related Applications

5

This application claims the benefit of the earlier
filing date of U.S. Patent Application No. 09/470,258, filed
on Dec. 22, 1999 and converted to a Provisional Application
by petition under 35 CFR 1.53(c)(1) on March 17, 2000. The
entire disclosure of the above-mentioned application is
incorporated herein by reference. ~~This application is also
a continuation in part of U.S. Patent Application No.
08/597,724, filed on February 7, 1996, the entire disclosure
of which is incorporated herein by reference.~~

Background of the Invention

The present invention relates to telemetry systems,
and, in particular, to transmission of telemetry data
through a network connection, such as an internet
connection, to a data processing center.

Metering is the periodic measurement of a parameter
at multiple locations. For example, utility companies meter
the natural gas, electricity and water consumed by
households. The cost of electricity can vary throughout the
day, as utility companies often wish to charge different
rates at different times of the day. For example, an
electrical utility company may wish to charge higher rates
during peak hours of consumption, e.g., the morning and

evening. In addition, electrical utility companies may wish to apply a penalty if a consumer exceeds a certain limit within a particular period of time.

The collection of data from a metering system is often performed by physical inspection of individual meters. For example, in residential areas, electrical utility companies use electromechanical meters with rotating disks to measure the consumption of electricity. Electrical utility companies send a "meter reader" to record the meter measurement about once a month. Metering of natural gas and water is handled similarly.

The physical inspection of meters by the meter readers on a frequent basis is expensive. Therefore, an automated system to electronically transmit metering information could provide considerable cost savings for frequently read meters.

Summary of the Invention

In general, in one aspect, the invention features a data collection system having a plurality of telemetry devices and collection devices. The telemetry devices have a sensor configured to generate a series of successive measurements by measuring a parameter at a series of measurement times, a memory configured to store a plurality of measurements from the series of successive measurements, and a transmitter configured to transmit measurements stored in memory to a collection device. The collection devices

have a hub to receive transmissions from the sensor, and a network device to forward a subset of a series of transmissions over a network connection to a data processing center to generate an output function.

5 Implementation of the invention may include one or more of the following features. The network connection may be an internet connection. The network device may comprise an internet interface, and the internet interface may comprise an e-mail client, a Hypertext Transmission Protocol
10 (HTTP) server, or a telnet daemon. The sensor may have a counter for storing a value, means for incrementing the counter upon receipt of a trigger signal, and means for storing the value from the counter in the memory and resetting the counter at different measurement times. The
15 telemetry devices may include a first timer having a predetermined time interval wherein the expiration of the predetermined time interval may cause the sensor to generate a measurement. The hub may comprise a radio-frequency local area network (LAN) transceiver or a power line carrier LAN
20 transceiver. The network device may be electronically connected to the hub. The data processing center may forward one or more commands through the network connection to the hub.

25 In another aspect, the invention is directed to a method of collecting data, including receiving a series of successive measurements from a series of transmissions from a telemetry device, storing and filtering the series of

successive measurements, and transmitting the filtered data through an internet connection to a processing center.

Implementation of the invention may include time stamping the filtered data, storing the filtered data, and forwarding the filtered data to an internet interface. The step of transmitting the filtered data through the internet connection may include triggering an e-mail to forward a subset of the stored filtered data, and the step of triggering the e-mail may include sending data after a predetermined period of time or sending data after receiving a predetermined number of packets. The step of transmitting the filtered data through the internet connection may include dialing an internet service provider (ISP) to establish a point-to-point protocol (PPP) connection.

In another aspect, the invention is directed to a network device connected to a receiving device configured to collect data generated by a plurality of sensors. The network device has a microprocessor to process data, at least one storage device to store data, and a transmitter to transmit data through an internet connection to a data processing center.

Implementation of the invention may include one or more of the following features. The network device may be connected to the receiving device using a serial port. The transmitter may transmit data to the internet via an ethernet connection. The transmitter may transmit data to the internet via a wireless Internet Protocol (IP) or a

dial-up PPP connection. The network device may have a multiplexer to route data between the microprocessor and the transmitter. The network device may be connected to the internet by a dial-up PPP connection through an ISP. The
5 network device may host at least one web page to display configuration information or data generated by the plurality of sensors. The network device may be installed in a location behind a corporate firewall.

In another aspect, the invention is directed to a
10 network device configured to collect data generated by a plurality of sensors. It includes a computer program having instructions for causing the device to interface with a LAN device, which receives data from the sensors. The program also includes instructions for causing the device to store
15 and forward data, and interface with a network connection to transmit data to a remote center.

Implementation of the invention may also include one or more of the following features. The computer program may include instructions to detect the arrival of data from the
20 plurality of sensors, process the data, and send commands to the LAN device to change an attribute value. The instructions to process the data may trigger an e-mail containing the processed data. The instructions to interface with the network connection may comprise
25 instructions to send data through an HTTP server or through a telnet daemon in response to a request.

In yet another aspect, the invention is directed to

a data collection system having a plurality of sensors each of which is configured to sample a parameter value at discrete measurement times. The sensors include a transmitter configured to transmit measured data. The
5 system further includes a collector having a receiver configured to receive data transmitted by the plurality of sensors, a processor configured to filter and store data received by the receiver from the plurality of sensors, and a transmitter configured to transmit the processed data to a
10 monitoring station by an internet connection.

In another aspect, the invention is directed to a data collection system having a plurality of measurement sensor means each located near a consumer of electricity for measuring data relating to consumer usage of electricity and
15 for transmitting the measured electricity usage data. The system further includes a collector means having a receiver for receiving electricity usage data transmitted by the plurality of sensor means, a processor for computing electricity usage information from electricity usage data
20 received by the receiver, and a transmitter for transmitting the electricity usage information to a monitoring station through an internet connection.

In yet another aspect, the invention is directed to a network for collecting data generated by a plurality of
25 sensors. The network includes a plurality of data generating devices having a sensor to measure a parameter to generate measurements, a memory configured to store the measurements,

and a transmitter to transmit the stored measurements to an intermediate device at a plurality of transmission times, there being fewer intermediate devices than data generating devices. The intermediate devices have a receiver to

5 receive transmissions from a subset of the data generating devices, a processor to filter the measurements from the transmissions and analyze the measurements to generate a metered function of the parameter, and a transmission module to transmit the metered function over an internet
10 connection. The network further includes a data station to receive transmitted metered functions from the plurality of intermediate devices.

In another aspect, the invention is directed to a method of collecting data comprising the steps of generating
15 measurements by measuring a parameter using a telemetry device, storing a plurality of the measurements in a memory, transmitting the stored measurements to a collection device, processing the transmitted measurements at the collection device, and transmitting, under a plurality of triggering
20 conditions, the processed measurements to a monitoring station by a network connection.

Implementation of the invention may include one or more of the following features. The method may include storing an old number in the collection device, generating a
25 new number in the telemetry device for each generated measurement, and comparing the old number to determine which measurements are new measurements not previously received by

the collection device and whether there are any missing measurements. The invention may also include storing the old number in the telemetry device wherein the step of generating the new number includes incrementing the old number.

In yet another aspect, the invention is directed to a method of collecting data including the steps of receiving a series of successive measurements from a series of transmissions from a telemetry device, storing and filtering the series of successive measurements by a pathway device connected to a LAN transceiver capable of receiving the series of transmissions, and transmitting the filtered data through an internet connection to a remote center for generation of a metered output function at the remote center.

In implementing the invention, the remote center may be a data processing center or a customer site.

The advantages of the invention include the following. The metering system provides metering without physical inspection of the individual meters and uses wired or wireless communication channels to transmit information. In addition, the metering system is cost-effective and reliable; it can be configured to be resistant to power failures; and it can be adaptable to a variety of applications and equipment provided by different vendors.

Furthermore, this invention capitalizes on the wide availability of the internet, or other equivalent wide area

networks, for transferring information to a remote processing center without incurring additional significant network layout costs. Also, by shifting the processing of data to a remote center, the system can be implemented with
5 a simple pathway device which serves only as a forward/storage thread, and which can be supplied by different vendors. However, the invention is also useful where the data is processed at an intermediate level, and the processed data is transmitted to a remote processing
10 center over an Internet connection.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of
15 the invention may be realized by means of the instrumentalities and combinations particularly pointed out in the claims.

Brief Description of the Drawings

The accompanying drawings, which are incorporated in
20 and constitute a part of the specification, schematically illustrate the invention, and together with the general description given above and the detailed description given below, serve to explain the principles of the invention.

FIG. 1 is an overall diagram of a telemetry
25 transmission system according to the present invention.

FIG. 2 is a schematic diagram of a meter of FIG. 1.

FIG. 3A is a schematic diagram of the hardware components of a pathway device of FIG. 1

FIG. 3B is a schematic illustration of the software components inside the pathway device of FIG. 1.

5 FIG. 4A is a flow diagram of the processing steps of a Local Area Network (LAN) device abstraction thread of the pathway device.

 FIG. 4B is a supplementary flow diagram of the processing steps of the LAN device abstraction thread of the
10 pathway device.

 FIG. 5 is a schematic illustration of the Store/Forward thread of the pathway device.

 FIG. 6 is a schematic illustration of the information exchanged among the various threads of the
15 pathway device.

 FIG. 7 is a sample web page hosted by the pathway device.

Description of the Invention

20 A metering or data collection system according to the present invention may be used in a variety of applications, such as utility metering, manufacturing control, traffic monitoring, vending machine monitoring, copy machine monitoring, event monitoring, and
25 meteorological data gathering. Data gathered by the collection system include electricity usage (kilowatt-hours), natural gas flow (cubic feet), water flow (cubic

feet), temperature ($^{\circ}\text{C}$), pressure (Torr), humidity (partial pressure), wind speed (miles per hour), precipitation (inches), voltage (volts) and current (amperes), all of which can be quantified by a measuring device in terms of pulse counts, analog voltage level, or multi-byte digital values, etc.

As shown in FIG. 1, a metering system or network 100 has at least a plurality of meters ("M"), or end-point devices, 10, 11, 12, 13, 14, 15, 16, 17 situated at sites #1, #2, and #3. Although FIG. 1 shows only eight meters, system 100 potentially can monitor the readings of hundreds of thousands of meters. The meters are located as required for a particular application. For example, an electrical utility company could place one meter at each house in a residential neighborhood to measure electrical energy consumption. Each meter may be constructed similarly as described below.

A set of collection devices 20-22 receive transmissions from meters 10-17. Each collection device includes a transceiver and a pathway device. The transceivers included in the collection device can be a variety of Local Area Network (LAN) transceivers, including, but not limited to, radio frequency local area network transceivers (RF LAN Transceiver) 30 and 32 manufactured by CellNet of San Carlos, California, or a power line carrier LAN transceiver 31. The transceivers can also include infrared LAN transceivers.

Each collection device 20-22 receives transmissions from one or more meters. In general, the likelihood of a successful transmission from a meter to a collection device is correlated with the distance between that collection device and that meter. In one implementation of network 1, the transmissions from a meter in the set of meters 10-17 may be received by the transceivers of more than one collection device. Since the redundant reception of the same transmission from a meter is inefficient, the collection devices are coordinated to eliminate such redundancy. The coordination works as follows: the first time a collection device receives a transmission from a particular meter, that collection device begins to process the transmission to measure the effective signal strength and estimate the radio link reliability for that meter. Each collection device that discovers this particular meter will process the transmission in a similar fashion. Upon comparing the processed results, the collection device that has indicated the strongest signal will be designated the "tracking collection" for this particular meter. Any other collection devices that have discovered the same meter are commanded to "untrack" that meter. Each collection device will have a database storing the addresses of the meters that are tracked and untracked. A collection device will only process data from a "tracked" meter.

Connected to LAN transceivers 30-32 are pathway devices 40-42. The connections are, in one implementation,

serial connections, such as Recommended-Standard 232 (RS-232) or Recommended-Standard 485(RS-485). In another implementation, the connections can be other equivalent types of interfaces.

5 Pathway devices 40-42 also have various internet interfaces for connecting to the Internet, or any other equivalent network. Pathway device 40 is connected to Internet 50 by an Ethernet connection 52. Ethernet connection 52 is a part of a corporate LAN and is located
10 behind a firewall 45, which runs proxy services for the corporate LAN and provides a connection 55 to Internet 50. Pathway device 41 is connected to Internet 50 through a wireless connection 54. Pathway device 42 is connected to Internet 50 by a dial-up point-to-point protocol (PPP)
15 connection over a telephone line on a public-switched telephone network (PSTN). The network connections 54, 55, or 56 can be either static internet connections using a always-on corporate LAN, Digital Subscriber Line (DSL) modem, cable modem or others, or they can be Dynamic Host
20 Configuration Protocol (DHCP) connections which are not continuously connected to Internet 50. Pathway devices 40-42 filter transmissions from meters 10-17 and forward the transmissions to data processing center 60 over Internet 50 or other equivalent networks.

25 Data processing center 60 may alternatively be termed a monitoring station or central station. Data processing center 60 also sends command messages to

collection devices 20-22 to, for example, change attributes of LAN transceivers 30-32. In cases where the data processing center 60 has not been a *priori* programmed with an understanding of the LAN transceiver protocol, the
5 pathway devices 40-42 will send Java byte code to the data processing center 60 when they communicate with the data processing center 60 for the first time. This byte code translates between the LAN transceiver data packet syntax and the syntax required by the data processing center. This
10 center 60 can alternatively be termed a monitoring center.

The data processing center 60 analyzes the periodic measurements by one or more meters 10-17 to generate a metered function. For example, an electrical utility company could request from the data center 60 the
15 electricity consumed each hour over the last twenty-four hours, the total amount of electricity consumed between 6 p.m. and 8 p.m. over the last month, or the time of peak electricity consumption in the previous day, at each house in a residential neighborhood.

20 In another embodiment, the pathway devices 40-42 can analyze the periodic measurements by one or more meters 10-17 to generate a metered function. The generation of metered functions at the collection device level is described in above-identified U.S. Patent Application Serial
25 no. 08/597,724.

Meters 10-17 periodically send their measurements to collection devices 20-22. In one implementation, meters 10-

17 accumulate and transmit the consumption of metered entity
on a pseudorandom basis over 300 times per day. The packets
transmitted in each transmission includes redundant data
transmitted in each of several previous transmissions. This
5 temporal redundancy is desirable to improve system
reliability. Redundant data will be filtered by collection ←
devices 20-22 as explained below.

As mentioned earlier, each meter will have one
tracking collection device in one implementation. These
10 transmissions may be any sort of wireless signals such as
radio frequency transmissions 160 or 162 (or other wireless
signals such as microwave or infrared), or wired signals
such as from a power line carrier 161, phone line wiring, or
custom wiring. Each collection device receives
15 transmissions from one or more meters. For example,
collection device 20 receives transmissions from meters 10-
12. A collection device may receive transmissions from one
to several thousand meters, limited only by the volume of
data traffic that LAN can sustain. Although FIG. 1 shows
20 only three collection devices, system 100 may include
hundreds or thousands of collection devices, depending upon
the number of meters in system 100.

At the data processing center 60, the periodic
measurements are analyzed to generate a metered function of
25 the measured parameters. The metered function information
could be the minimum, maximum or average value of the
parameter over a certain time period. The intelligence in

the data processing center 60 permits the use of inexpensive meters 10-17 which may only have processing power to perform measurements and transmit the measurements to inexpensive collection devices 20-22. As mentioned above, the

5 intelligence in the data processing 60 can also be shifted to collection devices 20-22 to have the generation of metered functions be conducted by pathway devices 40-42 in another implementation.

Referring to FIG. 2, each meter, e.g., meter 10,
10 includes a microprocessor 35, a parameter sensor 34, a power supply 33, a clock 36, a memory 38, and a transmitter 46. In another implementation, meter 10 may also have a receiver. Memory 38 includes several registers 43 and a pulse counter 44. Registers 43 and counter 44 store
15 measurements from sensor 34. In one embodiment of meter 10, memory 38 has eighteen registers. Memory 38 is constructed of non-volatile memory devices, such as erasable programmable read-only-memory chips (EPROMS), so that stored measurements are not lost if the power to power supply 33
20 fails.

Meter 10 measures the parameter at a series of measurement times. In normal operations, a set time interval T_{int} , such as 2.5 minutes, separates each measurement time. Meter 10 can be configured either as a
25 pulse accumulator meter or as a sampling meter. In the pulse accumulator mode, sensor 34 is triggered by a change in the parameter. Each time that sensor 34 is triggered,

the sensor sends a pulse to processor 35. In response to the pulse, processor 35 increments counter 44. At the expiration of time interval T_{int} , as measured by clock 36, the content of counter 44 is stored in a register and the counter is cleared. In the sampling mode, sensor 34 does not automatically send signals to processor 35 when the parameter changes. Instead, sensor 34 continuously monitors the parameter, and processor 35 periodically, e.g., at the expiration of time interval T_{int} , samples the sensor to receive a measurement. Processor 35 stores the measurement in counter 44.

Whether configured as a pulse accumulator meter or a sampling meter, the measurements by sensor 34 are stored in memory 38. At the expiration of time interval T_{int} , processor 35 discards the oldest measurement stored by register set 43 and places the newest measurement from counter 44 into the empty register.

Meter 10 transmits its stored measurements to collection device 20 at a series of transmission times. Memory 38 stores a transmission frequency N_{sup} which represents the number of measurement times per transmission. Processor 35 triggers a transmission time after N_{sup} measurements. At the transmission time, processor 35 causes transmitter 46 to transmit the contents of registers 43 to collection device 20.

In one embodiment, a pulse-accumulator meter is retrofit to an existing electromechanical meter used by most

electrical utility companies. Electromechanical meters use the flow of electricity to rotate a metal disk. The disk turns dials on the meter register to show the total consumption of electricity.

Sub 5
Sensor 34 and other components of meter 10 are described in more detail in above-identified U.S. Patent Application Serial No. 08/597,724.

The configuration of meter 10 as a pulse accumulator meter or as a sampling meter will depend on the intended application of system 500. Similarly, many sorts of sensors could be used with the present invention, depending on the application of system 500. For example, in a traffic monitoring system, a pulse accumulator meter could be used to count the number of automobiles that travel over a particular road. Such a pulse accumulator meter could use a pneumatic line as a sensor. As another example, in a weather monitoring system, a sampling meter could be used to periodically sample the atmospheric temperature. Such a sampling meter could use a thermocouple as the sensor.

After each transmission, collector 20 will examine the "new" measurements, i.e., the measurements in the most recent transmission which were not included in the previous transmission. Collector 20 may ignore the "old" measurements. Because a sequence number counter is incremented with each measurement, the number of new measurements in a transmission is indicated by the sequence number. If no transmissions are missed, the difference

between the old and new sequence numbers will equal the transmission frequency N_{sup} . For example, if N_{sup} equals two, and no transmissions are missed, then only the two most recent measurements will be new. However, if several
5 transmissions are missed, then the difference between the sequence numbers may be greater than two. Additionally, an alignment timer is driven by clock 36 to count down a delay time between a measurement time and a transmission time. Another variable stored in memory 38 is an alignment time
10 variable, T_{align} , which represents a delay between the measurement time and the actual transmission time.

Referring to FIG. 3A, pathway device 40, for example, includes a microprocessor 62, such as MC68EN302 manufactured by Motorola. Pathway device 40 also includes a
15 non-volatile memory (such as FLASH memory) 66, a random access memory (RAM) 65, a real-time clock 64, two serial ports 67 and 68, and one Ethernet port 69. The pathway device may use either Ethernet port 69 to connect to Internet 50, or a phone line and modem 55 to connect to the
20 Internet through serial port 68. The number of serial and Ethernet ports shown here are for illustrative purposes only and can vary in different implementations. The pathway device 40 in general provides a way to send telemetry data from a serially connected transceiver 30 available from a
25 variety of vendors, such as from CellNet of San Carlos, California, through an internet connection to a data processing/monitoring center.

Referring to Fig. 3B, the major software components in the pathway device 40 are shown. Pathway device 40 is connected to LAN transceiver 30 of collection device 20 by a serial connection 70 in one implementation. However,

5 pathway device 40 and LAN transceiver 30 can be connected by a variety of other connections suitable for connecting devices which are situated in close physical vicinity, such as parallel connection or memory map configuration.

Referring back to Fig. 3A, in one aspect, LAN transceiver 30
10 functions as a hub to which meters 10-12 are connected.

Upon receiving transmissions from meters 10-12, LAN transceiver 30, or hub, uses serial port 67 or 68, such as serial connection Recommended Standard-232 (RS232) or Recommended Standard-485 (RS485), to send data to, or
15 receive commands from, the pathway device 40. In one implementation, the pathway device 40 sends synchronous packets to LAN transceiver 30 to initiate communication, and LAN transceiver 30 responds synchronously to each message.

The synchronous packets are, in one implementation, for the
20 purpose of configuring status requests, and they are always responded to. LAN transceiver 30 also initiates asynchronous packets to pathway device 40 when the LAN radio successfully receives and interprets an RF packet and sends the data to the pathway device 40. The asynchronous packets
25 are not sent at regular intervals, and they are not responded to.

Inside the pathway device's multi-threaded main process 75, there are three major threads: LAN device abstraction thread, or LAN interface thread 78, store/forward thread 80, and an interface thread including interface multiplexer 82 and address code multiplexer 84. Communication among threads within a process can be by either shared memory or sockets. Internet interfaces 90 including e-mail client 92, Hypertext Transmission Protocol (HTTP) server 94, and telnet daemon 96 form a different process. Internet interfaces 90 can be provided by third-parties as separate processes. E-mail client 92 either uses another remote e-mail server provided by an Internet Service Provider (ISP) or an e-mail server connected to a corporate LAN, or e-mail client 92 uses an internal e-mail server 100 included in pathway device 40. Via the different channels, Internet interfaces 90 transmit data through the Transmission Control Protocol/Internet Protocol (TCP/IP) stack 102 to data processing center 60. Command messages are also forwarded to the pathway devices using the same channels.

If an authorized field representative or any other authorized party wishes to access data available at the pathway device 40, they may log on to pathway device 40 through the telnet daemon 96, or by accessing one or more web pages supported by HTTP server 94. FIG. 7 is a sample web page supported by the HTTP server 94. Their logon-username is associated with the packet's destination code

applied by accept/reject filter 114, to restrict their access only to that of data with the matching destination code. For example, the authorized representative can tell from this web page whether a packet has been forwarded to

5 the data processing center 60. For example, notice 150 states that packets which have not been e-mailed in a while are the white rows, as opposed to the shaded rows which represent packets which have already been mailed. The column headings for each row includes the time the packet is
10 stamped (152), the index value of the packet (154), the LAN address of the meter which transmitted this packet (156), the protocol ID (158), the length of the message (160), the flag value (162), the packet length (164) and the payload for the message (166). While the majority of the data is
15 forwarded to data processing center 60 through e-mail client 92, data processing center 60 or the authorized field representative may wish to check for missing data, or check for data before transmission time, by accessing telnet daemon 96 and/or HTTP server 94.

20 Referring to FIGS. 4A and 4B, the LAN interface thread 70 has three major functions: (1) to process received data from meters 10-12, (2) to send commands to LAN transceiver 30, and (3) to send JAVA byte code to the data processing center 60 to inform the center 60 how to format
25 messages to LAN transceiver 30. When packets arrive from meters 10-12 through communications link 70 (step 110), thread 78 responds promptly to avoid handshake timeout

periods. Usually the incoming packets will have cyclical redundancy check (CRC) values which must be checked for data validity. Next, the type of packet just received will be determined (step 112). If the incoming message contains

5 data (as opposed to an event message or a command response),

then the data will be forwarded to the accept/reject filter ←

(step 114). The pathway devices have a programmable filter designed to accept or reject data according to a pre-defined field-dependent criteria, such as the LAN address of the

10 meter which transmitted the data. Some data coming from some sensors will also be rejected by the filter because of the overlapping LAN transceivers and pathway devices attending to the same sensors. The redundant data submitted ←
by the same meter, on the other hand, will not be rejected.

15 Accepted data will be time-stamped (step 116) to record the date and time of day that it arrived. The table with pre-defined field-dependent criteria also contains optional destination codes defining the recipient to which the data will ultimately be sent. The possible destinations include

20 a data processing center or various customers. Rejected data are discarded. The data and accompanying timestamp are stored at the pathway device 40 before being forwarded to the data processing center 60. At decision point 118, thread 70 decides whether or not to forward the data

25 immediately. If the data is not to be forwarded immediately, the data goes to store/forward thread 80 for storage (step 124). Otherwise, the store/forward thread is

signaled to send all data now (step 122). The test used at decision point 118 is based on packet values such as those in the ID field.

5 If the incoming message is an event or a response to a previous command message, pathway device syntax codes are wrapped around the message (step 126) and the entire packet is forwarded to internet interface multiplexer 82 (step 128) through a socket.

10 If commands are received from the data processing center 60, thread 78 follows the steps outlined in FIG. 4B. Thread 78 receives commands from internet interface multiplexer 82 (step 129), extracts LAN protocol syntax from pathway command messages (step 130), and forwards them for output to the LAN transceiver (step 132). In one
15 implementation, when the data processing center 60 wishes to change an attribute value on the LAN transceiver 30 , it sends Java byte codes to assemble a command message containing all the required field values. This command message is then wrapped with the pathway device header, and
20 directed to the interface thread 78. These commands can also send messages over the LAN to telemetry devices which are capable of receiving messages. Additionally, when a pathway device 40 is first installed, the device 40 is announced to the data processing 60 ("discovery"). Thread
25 78 sends JAVA interface byte code describing LAN syntax to data processing center 60. In this manner, LAN transceivers

by various vendors with different LAN syntax can be incorporated into system 500.

FIG. 5 explains in detail the functionalities of the store/forward thread 80. Thread 80 stores received and filtered data packets from step 124 of FIG. 4A and forwards them to the recipient defined by the destination code which was optionally appended by the accept/reject filter 114.

Packets without a destination code will be sent to the data processing center 60. There is a configurable table

associating destination codes with valid eMail addresses and logon usernames. The packets can be forwarded as soon as they arrive, but storage is required in those where the pathway device is not continuously connected to the

Internet. The main storage device of thread 80 is non-volatile memory 140. Each incoming data packet is stored (step 144) with an index value and two flags, indicating "data sent" or "data acknowledged." After a data is sent (step 142) it is flagged as having been sent. The index is used by the data center 60 to check for missing packets.

Packets are not automatically deleted after being sent to data center 60. They are only dropped after non-volatile memory 140 is full and they are the oldest time-stamped packets in storage.

Thread 80 also contains e-mail trigger 150. A timer for triggering e-mail can be part of the microprocessor 62. Alternatively, e-mail triggers can be coming from real-time clock 64. SEND IMMEDIATELY signals coming from step 122 of

FIG. 4A will also trigger FLASH memory 140 to send specified records (step 142). There are a variety of triggering conditions to cause a pathway device to send out e-mail messages to the destination, such as data processing center 60. Messages can be sent after a certain number of minutes, after receiving a certain number of packets, or periodically at fixed times. Both previously unsent packets as well as unacknowledged packets are sent at each trigger. Sometimes intermediate mail servers in the Internet are improperly configured and can lose e-mail messages. Since the thread 80 re-sends unacknowledged packets, the data processing center improves its chances of recovering lost or delayed e-mail messages. If the delayed e-mail message eventually reaches the data processing center, the index values are used to reject duplicate data.

Thread 80 also sends Java interface byte code describing store/forward thread syntax to data processing center 60 (step 152) upon discovery, as explained above.

FIG. 6 shows the message routing between the Internet interfaces 90, threads 70, 80, and multiplexers 82 and 84. Address code multiplexer 82 tags the incoming internet packets and remembers which interface they came from, and directs commands from the data processing center 60 to either thread 70 or thread 80. Commands to thread 80 would be used to adjust its parameters (such as e-mail trigger thresholds), or to check its status. Commands to thread 70 would be used to configure the LAN transceiver or

to send messages to telemetry devices with reception capability. Interface multiplexer 84 determines which of the network interface protocols (e-mail, web pages, tenet terminal emulation) to use for messages to data processing center 60 and/or other destinations, and formats the stored packets according to the chosen interface specification. Interface multiplexer 84 also receives data, events, or command response from store/forward thread 80, or command responses and events from LAN device thread 78.

10 In summary, the metering system of the present invention monitors multiple meters. Each meter periodically measures a parameter, such as electricity consumption, and stores the sequence of measurements. Each meter periodically transmits the contents of its registers to a collector by wireless or wired signal. When a collector receives a transmission, it time stamps and stores those messages which pass through its filter. When any of a number of triggers occurs, the stored messages are forwarded through a network connection to a data processing center or other authorized destinations. The data processing center determines which meter (indicated by LAN address) sent the transmission, extracts the previously unprocessed measurements, and then generates a metered function, such as a load profile, a time-of-use profile, or a demand profile. 20 The data processing center can compensate for missed transmissions and power failures. The steps of generating the metered function at the collection level is explained in 25

U.S. patent application serial no.08/597,724. The operator of the metering system determines how the metered functions are used by the processing center/monitoring station, e.g., an electrical utility company may have the monitoring
5 station generate a customer billing using the metered function.

The present invention has been described in terms of a preferred embodiment. The invention, however, is not limited to the embodiment depicted and described. Rather,
10 the scope of the invention is defined by the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220